



BS EN 14351-1:2006+A1:2010

WINDOWS AND EXTERNAL PEDESTRIAN DOORSETS WITHOUT RESISTANCE TO FIRE AND/OR SMOKE LEAKAGE CHARACTERISTICS

DECLARATION OF PERFORMANCE

THIS IS TO CERTIFY THAT

EXPRESS TRADE FRAMES

of

Unit 1 Navigation Way

Fleetwood

Lancashire

FY7 6RS

HAVE CONFORMED WITH EN 14351-1:A1:2010 ANNEX ZA

FOR

VERTICAL SIDING & CASEMENT WINDOWS AND DOORS INTENDED TO BE USED IN DOMESTIC AND COMMERCIAL LOCATIONS

INSTIGATING AND IMPLEMENTING A SYSTEM OF FACTORY PRODUCTION CONTROL COMPLYING WITH EN 14351-1:A1:2010 ANNEX ZA


PRODUCING A TECHNICAL FILE CONTAINING THE TEST REPORT AND PERFORMANCE INDICATION PAPERS FOR ALL COMPONENTS

INCLUDING THE FOLLOWING MANDATORY REQUIREMENTS

LOAD BEARING CAPACITY OF SAFETY DEVICES - Clause 4.8

THERMAL CHARACTERISTICS - Clause 4.12

DANGEROUS SUBSTANCES - Clause 4.6

Signed: 
Position: **MANAGING DIRECTOR**

Date: **13/01/18**



Express Trade Frames

Unit 1 Navigation Way

Fleetwood

Lancashire

FY7 6RS

13

EN 14351-1:A1:2010

WINDOWS AND EXTERNAL PEDESTRIAN DOORSETS WITHOUT

RESISTANCE TO FIRE AND/OR SMOKE LEAKAGE CHARACTERISTICS

System: Veka plc FS 70 and Matrix 70 PVCu Casement, Tilt & Turn & VS Windows,

Residential Doors, French Doors, BI-Fold Doors & In-Line Patio Doors

Characteristics	Declared Value
Dangerous Substances	None
Thermal Transmittance	≤ 3.2W/(m ² K)
Load Bearing Capacity of Safety Devices	Passed
Resistance to Wind Load	npd
Resistance to snow and permanent load	npd
Reaction to fire	npd
External Fire Performance	npd
Water tightness	npd
Impact Resistance	npd
Radiation Properties	npd
Acoustic Performance	npd
Air Permeability	npd

This declaration relates to a worst case scenario and as such all our products will give an equal to or better (lower) than performance to that quoted

Signed: 

Date: **13/01/18**

Position: **MANAGING DIRECTOR**